

PORTABLE DIRECT HEAT

GWSZ-Series

sealersales



Premium Unit - Lightweight for Sealing Thicker Materials

- Lightweight and easy to operate
- PTFE coated jaws for cleaning ease
- Equipped with adjustable heat control
- Seal width: 12mm (0.47")
- Seal length: 300mm (11.8" and 400mm (15.7")
- Seal style: serrated

Introducing our **GWSZ-Series Portable Direct Heat Sealers** — designed and manufactured in Germany for highest quality sealing. This lightweight sealer is perfect for sealing irregular or long packages. We recommend this unit for sealing materials such as cellophane, coated aluminum foil, Kraft paper and other thicker materials. Please note this unit cannot seal polyethylene material.

The GWSZ-series comes equipped with an adjustable temperature controller, enabling users to tailor the heat level according to the specific material being sealed. Allow a 5-10 minute warm-up time for the sealer to attain the optimal temperature before use. Please do not touch the jaws of the sealer until the unit has been turned off and allowed to cool down.

To achieve best results, follow these simple steps. Adjust the temperature to the desired setting and allow 5-10 minutes for the sealer warm up. Insert the material between the jaws. Close the jaws and release the jaw after a couple of seconds. Fine tune the timing as needed until you achieve a satisfactory seal.

SPECIFICATIONS	GWSZ-300	GWSZ-400
SEALING	DIRECT	DIRECT
POWER	110V / 350W	110V / 350W
SEAL WIDTH	12MM (0.47")	12MM (0.47")
SEAL LENGTH	300MM (11.8")	400MM (15.7")
SEAL STYLE	SERRATED ==	SERRATED ==
TEMPERATURE	122-428°F (50-250°C)	122-428°F (50-250°C)
DIMENSIONS (L x W x H)	11.8" x 13.8" x 4.3"	15.7" x 13.8" x 4.3"
WEIGHT	3-LBS	3-LBS