

TABLE TOP VACUUM CHAMBER SEALER

TC-420

sealersales



Perfect for All Day Sealing

- **Stainless Steel Construction**
- **Digital Control Panel**
- **Busch Vacuum Pump - Industry Leader**
- **Seal Bar Options: Left/Right or Front Only**
- **Clear See Through Lid**
- **Certified to Meet UL, CSA & NSF**

TC-420 is a stainless steel vacuum chamber machine ideal for sealing vacuum pouches used in the pharmaceutical, food, or electronic industries. The unit does not need an external compressor for operation. Simply place vacuum pouch into chamber with the open edge across the sealing bar. Close the lid to start the cycle and the lid will automatically open when cycle is completed. Vacuum time ranges from 10-30 seconds.

Optional features are available including, but not limited to: digital control panel, pump size, voltage, gas flush, soft air, custom chamber size and computerized water resistant control panel.

Machines are ETL, UL, NSF, CE, and CSA Certified. Machine is assembled in the US and equipped with a reliable Busch vacuum pump. The TC-420 includes a one year warranty.

We recommend this unit for heavy duty applications (all day continuous packaging). For customers with light to medium applications, please refer to the TC-280-series.

SPECIFICATIONS	TC-420F	TC-420LR
CHAMBER SIZE	19.8" W x 19.2"L x 5"+4"H	19.8" W x 19.2"L x 5"+4"H
SEAL LENGTH	17.7" (FRONT)	16.9" x 2 (LEFT/RIGHT)
SEAL WIDTH	3MM WITH CUT OFF / OPTION: 6MM	3MM WITH CUT OFF / OPTION: 6MM
VACUUM PUMP CAPACITY	21M ³ /H (1-1/4HP/1KW)	21M ³ /H (1-1/4HP/1KW)
VOLTAGE	110V/1PH/50HZ/15A	110V/1PH/50HZ/15A
MACHINE SIZE	20" X 21" X 21"	20" X 21" X 21"
WEIGHT	220-LBS	220-LBS



Optional
PNC-01 Board

ADDITIONAL OPTIONS

- **PNC-01 Microprocessor Control**
- **Soft Air**
- **Bi-Active Seal**
- **Air Assist Sealing**
- **Twim Beam Sealing**

