

TABLE TOP VACUUM CHAMBER SEALER

TC-280F

sealersales



Compact for Small Workspaces

- **Stainless Steel Construction**
- **Digital Control Panel**
- **Busch 08 Vacuum Pump - Industry Leader**
- **Bladder Activated Sealing**
- **Clear See Through Lid**
- **Certified to Meet UL, CSA & NSF**

Video Demo →



TC-280F is a stainless steel vacuum chamber machine ideal for sealing vacuum pouches used in the pharmaceutical, food, or electronic industries. The unit does not need an external compressor for operation. Simply place vacuum pouch into chamber with the open edge across the sealing bar. Close the lid to start the cycle and the lid will automatically open when cycle is completed. Vacuum time ranges from 15-30 seconds.

Optional features are available including, but not limited to: gas flush, soft air, electric cut off seal bar, custom chamber size, custom voltage and computerized water resistant control panel.

Machines are ETL, UL, NSF, CE, and CSA Certified. Machine is assembled in the US with a Busch pump.

We recommend this unit for customers with light to medium applications. For heavy duty applications (all day continuous packaging), please refer to the TC-420-series.

The TC-280F includes a one year warranty.

SPECIFICATIONS	TC-280F
CHAMBER SIZE	14.2" W x 15.2"L x 5.7"H
SEAL LENGTH	11.8"
SEAL WIDTH	3MM WITH CUT OFF / OPTION: 4MM
VACUUM PUMP CAPACITY	6M ³ /H (0.25KW)
VOLTAGE	110V/1PH/50HZ/15A
MACHINE SIZE	15" X 18" X 16"
WEIGHT	117-LBS

ADDITIONAL OPTIONS

- **PNC-01 Microprocessor Control**
- **Soft Air**
- **Bi-Active Seal**
- **Air Assist Sealing**
- **Twim Beam Sealing**



Optional
PNC-01 Board