

# TABLE TOP VACUUM CHAMBER SEALER

TC-520

sealersales



Equipped with Industry Leading Busch Pump

- **Stainless Steel Construction with Clear Viewport**
- **Digital Control Panel (PD-01)**
- **Busch Vacuum Pump - Industry Leader**
- **Seal Bar Options: Left/Right or Front Only**
- **Clear See Through Lid**
- **Certified to Meet UL, CSA & NSF**

**TC-520** is a stainless steel vacuum chamber machine ideal for sealing vacuum pouches used in the pharmaceutical, food, or electronic industries ensuring a longer shelf life, reduced spoilage and superior product presentation. The unit does not need an external compressor for operation. Simply place vacuum pouch into chamber with the open edge across the sealing bar. Close the lid to start the cycle and the lid will automatically open when cycle is completed. Vacuum time ranges from 10-30 seconds.

Optional features are available including, but not limited to: digital control panel, pump size, voltage, gas flush, soft air, custom chamber size and computerized water resistant control panel. Slant trays can replace the filler boards if you are working on products with liquids.

Machines are ETL, UL, NSF, CE, and CSA Certified. Machine is assembled in the US and equipped with the industry leading reliable Busch RB00021 vacuum pump. The TC-520 includes a one year warranty.

SPECIFICATIONS	TC-520F	TC-520LR
CHAMBER SIZE	21.2" W x 19.8"L x 4"+ 2.4"H	17.7" W x 21.2"L x 4"+ 2.4"H
SEAL LENGTH	21.3" (FRONT)	16.5" x 2 (LEFT/RIGHT)
SEAL WIDTH	3MM WITH CUT OFF / OPTION: 6MM	3MM WITH CUT OFF / OPTION: 6MM
VACUUM PUMP CAPACITY	21M <sup>3</sup> /H (0.75KW)	21M <sup>3</sup> /H (0.75KW)
VOLTAGE	110V/1PH/50HZ/15A	110V/1PH/50HZ/15A
MACHINE SIZE	24" X 30" X 22"	24" X 30" X 22"
WEIGHT	280-LBS	280-LBS



Optional  
PNC-01 Board

#### ADDITIONAL OPTIONS

- **PNC-01 Microprocessor Control**
- **Soft Air**
- **Bi-Active Seal**
- **Air Assist Sealing**
- **Twim Beam Sealing**
- **220V**

